



Wireless Cellular Router/Modem

[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - WIFI
 - Firewall
 - Administration

Select Language

English ▾

- [Status](#)
- [Statistic](#)
- [WIFI Statistic](#)
- [Management](#)



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - Ipsec
 - PPTP
 - L2TP
 - Tunnel
 - WiFi

Ethernet Port Status



Access Point Status

System Info	
Series	R586
SN	08641304562C
Software Version	2.3.31 (Apr 4 2013)
Hardware Version	1.0.0
System Up Time	6 min
Operation Mode	Gateway Mode

Cell Network Info	
Cell Modem	HUAWEI-EM820
IMEI/ESN	355858040265177
Sim Status	SIM ready
Selected Network	AUTO
Registered Network	Registered on Home network: "46000",0
Sub Network Type	EDGE



Wireless Cellular Router/Modem

[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
 - WiFi

Signal	26
Cell Status	DOWN
Internet Configurations	
Connected Type	CELL
WAN IP Address	
Subnet Mask	
Default Gateway	
Primary Domain Name Server	
Secondary Domain Name Server	
MAC Address	08:66:01:01:4E:A6
Local Network	
Local IP Address	192.168.8.1
Local Netmask	255.255.255.0
MAC Address	08:66:01:01:4E:A7
IPSEC Status	
Name	Status
PPTP Status	
PPTP	down
PPTP IP	
L2TP Status	
L2TP	down
L2TP IP	



Wireless Cellular Router/Modem

[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode**
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipsec
 - PPTP
 - L2TP
 - Tunnel
- WiFi

Operation Mode Configuration

You may configure the operation mode suitable for you environment.

- Bridge:**
All ethernet and wireless interfaces are bridged into a single bridge interface.
- Gateway:**
The first ethernet port is treated as WAN port. The other ethernet ports and the wireless interface are bridged together and are treated as LAN ports.
- AP Client:**
The wireless apcli interface is treated as WAN port, and the wireless ap interface and the ethernet ports are LAN ports.

Ethernet wan port as wan in AP Client Mode:

Ethernet wan port as lan in Cell Gateway Mode:

NAT Enabled:

TCP Timeout:

UDP Timeout:



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU**
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipsec
 - PPTP
 - L2TP
 - Tunnel
- WiFi

DTU Settings

DTU Status	
dtu status	off

DTU Serial setting	
serial baudrate	115200 bps
serial parity	none
serial databits	8 bits
serial stopbits	1 bits
serial flow control	none

DTU config	
mode	client
Protocol	tcp
server 1	<input checked="" type="checkbox"/> 192.168.8.100 : 5000
server 2	<input type="checkbox"/> 192.168.8.101 : 5000
server 3	<input type="checkbox"/> 192.168.8.102 : 5000



Wireless Cellular Router/Modem

[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRPP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WiFi

Link Backup

Operation Mode	
Active	<input type="checkbox"/>
Back To Higher Primary When Possible	<input checked="" type="checkbox"/>

Link Priority Settings	
WAN1: Cellular Wireless	<input type="checkbox"/> OFF <input checked="" type="radio"/> High Priority <input type="radio"/> Middle Priority <input type="radio"/> Low Priority
WAN2: Wifi DHCP Wireless	<input type="checkbox"/> OFF <input type="radio"/> High Priority <input checked="" type="radio"/> Middle Priority <input type="radio"/> Low Priority
WAN3 : Wired DHCP	<input type="checkbox"/> OFF <input type="radio"/> High Priority <input type="radio"/> Middle Priority <input checked="" type="radio"/> Low Priority

Link Check Settings	
Check Count	3 (1-20)
Check Interval Time(min)	2 (1-60)
Used The Same Method	YES
All WAN Check Method	ping ip

Apply



Wireless Cellular Router/Modem

[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
 - WiFi

GPS

GPS Settings	
GPS Active	<input type="checkbox"/>
GPS Send to	TCP/IP
GPS to Net Settings	
socktype	tcp
server	192.168.8.100
server port	6000

[apply](#)



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WiFi

SMS/Voice Settings

SMS/Voice Command Settings		
Message/Voice status	off ▾	
Fix Error For Some Network	<input type="checkbox"/>	
telephone number		
number 1	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM
number 2	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM
number 3	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM
number 4	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM
number 5	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM
number 6	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM
number 7	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM
number 8	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM
number 9	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM
number 10	<input type="text"/>	<input type="checkbox"/> SMS <input type="checkbox"/> VOICE <input type="checkbox"/> ALARM



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WiFi

VRRP

VRRP Settings	
VRRP Active	<input type="checkbox"/>
VRRP ID *	50 0~255
Priority *	100 1~255
Interval Time *	2 s
garp master delay *	0 s (0~1000)
Password	●●●●●●●●
Virtual IP *	192.168.8.254 :24
Source IP for Multicast	
Preemption Mode	<input checked="" type="checkbox"/>
control ipsec (only for backup)	<input type="checkbox"/>
VRRP Status	



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
- Internet Settings
 - WAN**
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WiFi

Wide Area Network (WAN) Settings

You may choose different connection type suitable for your environment. Besides, you may also configure parameters according to the selected connection type.

WAN Connection Type: Cell Network

Cell Mode	
Cell Modem	HUAWEI-EM820
Modem Description	HUAWEI WCDMA 3G modem
Network Type	AUTO
Online Mode	Keep Alive
Parameter Groups	WCDMA View Delete
Advance Parameter Groups	
Advance Cell Options	
MAC Clone	
Enabled	Disable

Apply Cancel



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN**
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
 - WiFi

Local Area Network (LAN) Settings

You may enable/disable networking functions and configure their parameters as your wish.

LAN Setup	
IP Address	<input type="text" value="192.168.8.1"/>
Subnet Mask	<input type="text" value="255.255.255.0"/>
LAN 2	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
LAN2 IP Address	<input type="text"/>
LAN2 Subnet Mask	<input type="text"/>
MAC Address	08:66:01:01:4E:A7
DHCP Type	Server
Start IP Address	<input type="text" value="192.168.8.100"/>
End IP Address	<input type="text" value="192.168.8.200"/>
Subnet Mask	<input type="text" value="255.255.255.0"/>
Primary DNS Server	<input type="text" value="168.95.1.1"/>
Secondary DNS Server	<input type="text" value="8.8.8.8"/>



Wireless Cellular Router/Modem

[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN**
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
 - WiFi

Secondary DNS Server	<input type="text" value="8.8.8.8"/>
Default Gateway	<input type="text" value="192.168.8.1"/>
Lease Time	<input type="text" value="86400"/>
Statically Assigned	MAC: <input type="text"/> IP: <input type="text"/>
Statically Assigned	MAC: <input type="text"/> IP: <input type="text"/>
Statically Assigned	MAC: <input type="text"/> IP: <input type="text"/>
802.1d Spanning Tree	Disable ▾
LLTD	Disable ▾
IGMP Proxy	Disable ▾
UPNP	Disable ▾
PPPoE Relay	Disable ▾
DNS Proxy	Enable ▾



Wireless Cellular Router/Modem

[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients**
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WiFi

DHCP Client List

You could monitor DHCP clients here.

DHCP Clients			
Hostname	MAC Address	IP Address	Expires in



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing**
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
 - WiFi

Dynamic Routing Settings

You may enable and disable dynamic routing here.

Zebra Settings

Reset Zebra

Change Zebra Password

old Passowrd

new Passowrd

RIP Dynamic routing Settings

RIP

Disable ▾

Change RIP Password



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List**
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
 - WiFi

Dynamic Routing List

You may view dynamic routing here.

Dynamic Routing List Select

Route Type ▼

dynamic routing list

no	flags	Destination	gateway	interface
0	C>*	127.0.0.0/8	0.0.0.0	lo
1	C>*	192.168.8.0/24	0.0.0.0	br0
2	K>*	255.255.255.255/32	0.0.0.0	br0

K - kernel route, C - connected, S - static, R - RIP, O - OSPF, B - BGP, > - selected route, * - FIB route



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP**
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
 - WiFi

SNMP

SNMP Settings	
SNMP Active	<input type="checkbox"/>
Contact Info	<input type="text"/>
Location	<input type="text"/>

SNMP V1 and V2c Settings	
user	<input type="text" value="public"/>
host/lan	<input type="text" value="0.0.0.0/0"/>
writable	<input type="checkbox"/>

SNMP V3 Settings	
user	<input type="text"/>
writable	<input type="checkbox"/>
Security mode	<input type="radio"/> None <input type="radio"/> Authorized <input checked="" type="radio"/> Private
Authentication	<input checked="" type="radio"/> MD5 <input type="radio"/> SHA
Encryption	<input checked="" type="radio"/> DES <input type="radio"/> AES
Authentication Password	<input type="password" value="••••••••"/>



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - IPsec
 - PPTP
 - L2TP
 - Tunnel
- WiFi

IPSEC VPN

IPSEC List						
Select	Name	Service Status	Gateway	Interface	Active Status	Link Status



[open all](#) | [close all](#)

- Router
 - Status
 - Operation Mode
 - DTU
 - Link Backup
 - GPS
 - SMS/Voice
 - VRRP
 - Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
 - VPN
 - IPsec**
 - PPTP
 - L2TP
 - Tunnel
 - WiFi

PPTP

PPTP VPN Settings	
PPTP IP	
PPTP VPN Active	<input type="checkbox"/>
PPTP User	pppoe_user
PPTP Password	●●●●●●●●
PPTP Server	
Remote Lan/Mask	/
Local PPTP IP	dhcp
MPPE Encryption	<input type="checkbox"/>



Wireless Cellular Router/Modem

- Link Backup
- GPS
- SMS/Voice
- VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP**
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List

L2TP

L2TP VPN Settings	
L2TP IP	
L2TP VPN Active	<input type="checkbox"/>
L2TP User	<input type="text"/>
L2TP Password	<input type="text"/>
L2TP Server	<input type="text"/>
Remote Lan/Mask	<input type="text"/> / <input type="text"/>
Local PPTP IP	dhcp <input type="text"/>
MPPE Encryption	<input type="checkbox"/>



- Link Backup
- GPS
- SMS/Voice
- VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List

Basic Wireless Settings

You could configure the minimum number of Wireless settings for communication, such as Network Name (SSID) and Channel. The Access Point can be set simply with only the minimum setting items.

Wireless Network		
Radio On/Off	RADIO OFF	
WiFi On/Off	WiFi OFF	
Network Mode	11b/g/n mixed mode	
Network Name(SSID)	Cell_AP_130455C7	Hidden <input type="checkbox"/> Isolated <input type="checkbox"/>
Multiple SSID1		Hidden <input type="checkbox"/> Isolated <input type="checkbox"/>
Multiple SSID2		Hidden <input type="checkbox"/> Isolated <input type="checkbox"/>
Multiple SSID3		Hidden <input type="checkbox"/> Isolated <input type="checkbox"/>
Multiple SSID4		Hidden <input type="checkbox"/> Isolated <input type="checkbox"/>
Multiple SSID5		Hidden <input type="checkbox"/> Isolated <input type="checkbox"/>
Multiple SSID6		Hidden <input type="checkbox"/> Isolated <input type="checkbox"/>



Wireless Cellular Router/Modem

- Link Backup
- GPS
- SMS/Voice
- VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List

HT Physical Mode	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
MBSSID AP Isolation	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
BSSID	08:66:01:01:4E:A8
Frequency (Channel)	2412MHz (Channel 1) ▾
HT Physical Mode	
Operating Mode	<input checked="" type="radio"/> Mixed Mode <input type="radio"/> Green Field
Channel BandWidth	<input type="radio"/> 20 <input checked="" type="radio"/> 20/40
Guard Interval	<input type="radio"/> Long <input checked="" type="radio"/> Auto
MCS	Auto ▾
Reverse Direction Grant(RDG)	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
Extension Channel	2432MHz (Channel 5) ▾
Space Time Block Coding(STBC)	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
Aggregation MSDU(A-MSDU)	<input checked="" type="radio"/> Disable <input type="radio"/> Enable
Auto Block ACK	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
Decline BA Request	<input checked="" type="radio"/> Disable <input type="radio"/> Enable
HT Disallow TKIP	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
Other	



- Link Backup
- GPS
- SMS/Voice
- VRRP
- Internet Settings
 - WAN
 - LAN
 - DHCP clients
 - Static Routing
 - Dynamic Routing
 - Dynamic Routing List
 - QoS
 - SNMP
 - Cell ICMP Check
 - Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List

Advanced Wireless Settings

Use the Advanced Setup page to make detailed settings for the Wireless. Advanced Setup includes items that are not available from the Basic Setup page, such as Beacon Interval, Control Tx Rates and Basic Data Rates.

Advanced Wireless	
BG Protection Mode	Auto
Beacon Interval	100 ms (range 20 - 999, default 100)
Data Beacon Rate (DTIM)	1 ms (range 1 - 255, default 1)
Fragment Threshold	2346 (range 256 - 2346, default 2346)
RTS Threshold	2347 (range 1 - 2347, default 2347)
TX Power	100 (range 1 - 100, default 100)
Short Preamble	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Short Slot	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Tx Burst	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Pkt_Aggregate	<input checked="" type="radio"/> Enable <input type="radio"/> Disable



- Static Routing
- Dynamic Routing
- Dynamic Routing List
- QoS
- SNMP
- Cell ICMP Check
- Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security**
 - WDS
 - WPS
 - Station List
 - Statistics
- Firewall
 - MAC/IP/Port Filtering
 - Port Forwarding
 - DMZ
 - System Security
 - Content Filtering
- Administration

Wireless Security/Encryption Settings

Setup the wireless security and encryption to prevent from unauthorized access and monitoring.

Select SSID	
SSID choice	Cell_AP_130455C7 ▾
"Cell_AP_130455C7"	
Security Mode	Disable ▾
Access Policy	
Policy	Disable ▾
Add a station Mac:	<input type="text"/>



- Static Routing
- Dynamic Routing
- Dynamic Routing List
- QoS
- SNMP
- Cell ICMP Check
- Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List
 - Statistics
- Firewall
 - MAC/IP/Port Filtering**
 - Port Forwarding
 - DMZ
 - System Security
 - Content Filtering
- Administration

MAC/IP/Port Filtering Settings

You may setup firewall rules to protect your network from virus, worm and malicious activity on the Internet.

Basic Settings	
MAC/IP/Port Filtering	Disable ▾
Default Policy -- The packet that don't match with any rules would be:	Dropped ▾

MAC/IP/Port Filter Settings	
Source MAC address	<input type="text"/>
Dest IP Address	<input type="text"/>
Source IP Address	<input type="text"/>
Protocol	None ▾



- Static Routing
- Dynamic Routing
- Dynamic Routing List
- QoS
- SNMP
- Cell ICMP Check
- Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List
 - Statistics
- Firewall
 - MAC/IP/Port Filtering
 - Port Forwarding
 - DMZ
 - System Security
 - Content Filtering
- Administration

Virtual Server Settings

You may setup Virtual Servers to provide services on Internet.

Port Forwarding	
Port Forwarding	Disable ▾
IP Address	<input type="text"/> : <input type="text"/>
Port Range	<input type="text"/> - <input type="text"/>
Protocol	TCP&UDP ▾
Interface	WAN ▾
Comment	<input type="text"/>

(The maximum rule count is 32.)

Current Port Forwarding in system:					
No.	IP Address	Port Range	Protocol	Interface	Comment



- Static Routing
- Dynamic Routing
- Dynamic Routing List
- QoS
- SNMP
- Cell ICMP Check
- Lo Interface
- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List
 - Statistics
- Firewall
 - MAC/IP/Port Filtering
 - Port Forwarding
 - DMZ
 - System Security
 - Content Filtering
- Administration

System Security Settings

You may configure the system firewall to protect AP/Router itself from attacking.

Remote management	
Remote management (via WAN)	Allow ▾
Ping form WAN Filter	
Ping form WAN Filter	Disable ▾
Block Port Scan	
Block port scan	Disable ▾
Block SYN Flood	
Block SYN Flood	Disable ▾
Stateful Packet Inspection (SPI)	
SPI Firewall	Disable ▾



- VPN
 - Ipssec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List
 - Statistics
- Firewall
 - MAC/IP/Port Filtering
 - Port Forwarding
 - DMZ
 - System Security
 - Content Filtering
- Administration
 - Management
 - Upload Firmware
 - Settings Management
 - System Command
 - System Log
 - Statistics
 - Reboot

Content Filter Settings

You can setup Content Filter to restrict the improper content access.

Webs Content Filter

Filters: Proxy Java ActiveX

Webs URL Filter Settings

Add a URL filter:

URL:

Current Webs URL Filters:

No	URL



- VPN
 - Ipsec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List
 - Statistics
- Firewall
 - MAC/IP/Port Filtering
 - Port Forwarding
 - DMZ
 - System Security
 - Content Filtering
- Administration
 - Management**
 - Upload Firmware
 - Settings Management
 - System Command
 - System Log
 - Statistics
 - Reboot

System Management

You may configure administrator account and password, NTP settings, and Dynamic DNS settings here.

Language Settings

Select Language	English ▾
-----------------	-----------

Administrator Settings

Account	admin
Password	•••••
WatchDog	<input checked="" type="radio"/> Enable <input type="radio"/> Disable

Web Management Port Settings



- VPN
 - Ipsec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List
 - Statistics
- Firewall
 - MAC/IP/Port Filtering
 - Port Forwarding
 - DMZ
 - System Security
 - Content Filtering
- Administration
 - Management
 - Upload Firmware
 - Settings Management
 - System Command
 - System Log
 - Statistics
 - Reboot

System Log

Remote System Log Settings		
Remote System Log Active	<input type="checkbox"/>	
server	192.168.8.100	:UDP:514

apply

```
System Log
Jan 1 00:00:15 syslogd started: BusyBox v1.12.1
Jan 1 00:00:15 kernel: klogd started: BusyBox v1.12.1 (2013-02-23 15:19
Jan 1 00:00:15 kernel: Linux version 2.6.21 (root@localhost.localdomain
Jan 1 00:00:15 kernel:
Jan 1 00:00:15 kernel: The CPU frequency set to 360 MHz
Jan 1 00:00:15 kernel: CPU revision is: 0001964c
Jan 1 00:00:15 kernel: Determined physical RAM map:
Jan 1 00:00:15 kernel: memory: 04000000 @ 00000000 (usable)
Jan 1 00:00:15 kernel: Initrd not found or empty - disabling initrd
Jan 1 00:00:15 kernel: On node 0 totalpages: 16384
Jan 1 00:00:15 kernel: DMA zone: 128 pages used for memmap
Jan 1 00:00:15 kernel: DMA zone: 0 pages reserved
Jan 1 00:00:15 kernel: DMA zone: 16256 pages, LIFO batch:3
Jan 1 00:00:15 kernel: Normal zone: 0 pages used for memmap
Jan 1 00:00:15 kernel: Built 1 zonelists. Total pages: 16256
```



Wireless Cellular Router/Modem

- VPN
 - Ipsec
 - PPTP
 - L2TP
 - Tunnel
- WIFI
 - Basic
 - Advanced
 - Security
 - WDS
 - WPS
 - Station List
 - Statistics
- Firewall
 - MAC/IP/Port Filtering
 - Port Forwarding
 - DMZ
 - System Security
 - Content Filtering
- Administration
 - Management
 - Upload Firmware
 - Settings Management
 - System Command
 - System Log
 - Statistics
 - Reboot

Statistic

Take a look at the statistics

Memory	
Memory total:	60652 kB
Memory left:	31208 kB

WAN/LAN	
WAN Rx packets:	0
WAN Rx bytes:	0
WAN Tx packets:	6
WAN Tx bytes:	492
LAN Rx packets:	956
LAN Rx bytes:	99143
LAN Tx packets:	1276
LAN Tx bytes:	1105921

All interfaces	
Name	eth2
Rx Packet	1320
Rx Byte	163356
Tx Packet	1525
Tx Byte	1222420